New Holland Windrow Inverter Specifications

WEIGHT Base Unit Base unit + Hydraulics Base unit + Hydraulics + Extension		1080 lbs (490 kg) 1147 lbs (520 kg) 1409 lbs (639 kg)	GROUND CLEARANCE II Tine Tips Pickup Axle	N TRANSPORT POSITION 8.3" (211 mm) 12.3" (312 mm) 10.8" (274 mm)
WIDTH	Transport position	7' 10" (2377 mm)	WINDROW OFFSET DIS [•] Base unit off	TANCE
with Extension –	Field position Transport position	9' 1" (2997 mm) 8' 1" (2470 mm)	left side with Extension off	3'4"–6'8" (1000 mm – 2000 mm)
	Field position	14' 6" (4420 mm)	right side.	11' 0" (3353 mm)
LENGTH			PICKUP WIDTH	5' 5" (1650 mm)
with Hydraulics–	Transport position Field position Transport position	12' 4" (3759 mm) 11' 11" (3632 mm) 13' 4" (4064 mm)	MAXIMUM Transport speed	20 mph (32 km/hr)
with Extension –	Field position Transport position	12' 11" (3937 mm) 13' 4" (4064 mm)	OPERATING SPEED	2-8 mph (3-13 km/hr)
	Field position	12' 11" (3937 mm)	TIRE SIZE	5.00 x 15, 4 ply traction tread
HEIGHT Transport position 5' 10" (1778 mm)			ATTACHMENTS AND ACCESSORIES	
with Extension –	Field position Transport position Field position	4' 6" (1367 mm) 7' 7" (2312 mm) 4' 6" (1367 mm)	Cross-conveyor extension kit, Hydraulic drive kit, Hydraulic valve kit, Adaptor manifold kit, Pickup wheel kit, Dual wheel kit, Pickup speed increase sprocket.	

Visit our Web site at www.newholland.com/na. Or, call toll-free 866-NEW-HLND (866-639-4563).

Design, materials and/or specifications are subject to change without notice and without liability therefor. Specifications are applicable to units sold in Canada, the United States, its territories and possessions, and may vary outside these areas.

